



# inVENTer

## Pure Controller



### INTUITIVE:

3-stage ventilation control via toggle switch.

### VISIBLE:

Operating modes heat recovery and ventilation with LED status display.

### ORGANIZED:

Including LED display for changing the filter.

### ADJUSTED:

Double rocker also possible in your own switch design.

### RELIABLE:

Flat version for continuous operation in apartment buildings.

### SECURE:

Safety device available when operating with open fireplaces.

### Technical Data:

MAX. CONTROL OF IV VENTILATION UNITS [PIECES]	4
MAINS VOLTAGE [V AC] / [HZ]	230 / 50
OPERATING VOLTAGE [V DC]	24
POWER CONSUMPTION, MAX. [W]	18
PROTECTION CLASS	IP 20 / II

### Possibilities:

**Versions:** Pure

or Pure Flat (cannot be switched off)

**Power supplies:** flush-mounted power supply


or switch cabinet power supply

**External switch contact:**

Sensor (e.g. CO<sub>2</sub> sensor)

or safety device

### Components:



Control module



Power supply



Control unit double rocker (inVENTer-Design or own switch range)



inVENTer GmbH | Ortsstraße 4a | D-07751 Löberschütz  
Phone: +49 (0) 36427 211-0 | Fax: +49 (0) 36427 211-113  
E-mail: info@inventer.de | Web: www.inventer.eu