

X-Flow in the office



INDEPENDENT:

Automatic, sensor-controlled ventilation for individual rooms such as offices. Sensors for CO₂ level, temperature and humidity.

QUICKLY INSTALLED:

Only two core drill holes in the outer wall required per unit.

DIRECT:

Operation possible with connection to 230 V socket.

HIGH UP:

Installation in storey buildings at heights of up to 80 m.

EFFICIENT:

Air flow rate up to 180 m³/h.

A major part of the indoor heat is being recovered.

Technical details

WALL OPENING [Ø, mm]	2 x 180
AIR VOLUME FLOW [m ³ /h]	50 – 180
HEAT RECOVERY [%]	87
POWER CONSUMPTION MAX. [W]	33,4
SOUND PRESSURE LEVEL [dB(A)], 2 m	12 – 32
SPI [W/(m ³ /h)]	0,15
DIMENSIONS OF THE UNIT WxHxD [mm]	520x1945x202
ENERGY EFFICIENCY CLASS	A

Fresh air for the team

The X-Flow individual room ventilation particularly shines with its independent mode of operation. After installation in the outer wall and simple connection to a socket, the integrated sensors do the work. They dynamically adjust the air volume flow to the room climate. Its high air volume flow of 180 m³/h supplies the room with (prewarmed) fresh air, even when heads are smoking.